

# Technical Information

---

## Adhesin EL 633-1904SL

<b>TYPE:</b>	Waterborne synthetic emulsion
<b>PHYSICAL PROPERTIES:</b>	Appearance : White Viscosity : 8500 - 11500 cps (BF RVT 4/10/27 <sup>0</sup> C) Solids : 55 - 58 % S.G : 1.03 - 1.07 pH : 4 - 5 Flammability: Not flammable
<b>OPERATING CONDITIONS:</b>	Ready for use as supplied. Dilute with water when required. Direct transfer from brush, roller or glue spreader.
<b>SUGGESTED USES:</b>	Lamination of Al foil, films to paper, board etc suitable for high speed machines. It conforms to composition requirements of FDA regulation 21 CFR 175.105 "Adhesives".
<b>PRECAUTIONS:</b>	Store in closed containers to prevent drying out and contamination. Rotate stock - first in - first out. Do not mix with other adhesives. Recommended to use the adhesive within 6 months.
<b>PACKAGE:</b>	50 Kg HDPE Drum / 200 kg MS drum

### **Henkel CAC Pvt. Ltd.**

*Plot No. 1/1 Part 2, TTC Indl. Area, Thane Belapur Road  
Koparkhairne, Navi Mumbai- 400710.  
Tel : +91-22-27787371 Fax : +91-22-27780025*

